



Product information:

XIOS G
BED TYPE

SPECIFICATIONS

	XIOS G
Table length - mm	1.250 - 1.500 - 2.000
Table width - mm	1.250 - 1.500 - 2.000
Longitudinal travel - mm	2.500 - 3.000 - 4.000
Cross travel - mm	1.200 (1.600)*
Vertical travel - mm	1.200 (1.600 - 2.000)*
Min – max distance from table to spindle nose - mm	0 - 1.145 (1.545 - 1.945)*
Working Feed - mm/min	up to 15.000
Rapid feed - mm/min	30.000
Drives of X-Y-Z - mm	Ball screw
Power - kW	32 (40)*
Speed of the spindle head - min-1	3.000 (4.500-6.000)*
Positioning and repeatability accuracy - mm	0,008/4.000-0,005
Tool magazine	30 (40-60-80)*
Allowed weight on the table - kg	5.000 - 5.000 - 7.000
Approx. net weight - kg	25.000 - 50.000

(Optional) *

ACCESSORIES

	XIOS G
HEADS	
45° Automatic Head 360.000 pos, 0,001°	•
45° Automatic Head 360 x 1° - 144 x 2,5°	○
30° automatic head 360.000 pos. 0,001° / continuous rotation	○
30° automatic head, 360.000 positions each 0,001° / continuous rotation with electrospindle.	○
Change of heads	—
Coolant tank	1000 l, 30l/min - 22 bar / 60 l/min - 5 bar
Machine with two working tables	○
Milling - Turning	○

	XIOS G
Chip Conveyor	•
Complete enclosure open on top	•
Complete enclosure with ceiling	○

• Standard ○ Optional — No available

PRODUCT IMAGES



HEAD IMAGES



45° Automatic Head
360.000 pos, 0,001°



30° automatic head
360.000 pos. 0,001° /
continuous rotation



30° automatic head,
360.000 positions each
0,001° / continuous
rotation with
electrospindle.

RELATED APPLICATIONS



FRANCIS TURBINE
HYDROELECTRIC



CAPITAL GOODS
GENERAL MACHINING



DIE
MOULDS AND DIES



CAPITAL GOODS
LARGE COMPONENTS

Más información en www.zayer.com